

Claims

1. An optical network comprising:

sections for establishing optical paths;

5 a plurality of optical edge routers for connecting external IP networks to the optical network; and

a plurality of optical cross connects, for connecting the optical edge routers by the optical paths, having switching sections with respect to an optical pulse unit, wherein

each of the optical edge routers has both of:

10 an optical network control instance for maintaining topology information in the optical network and switching/signaling the optical paths; and

an IP network instance for maintaining a routing table in each of the external IP networks and activating routing protocols between the external IP networks and the IP network instance.

15 2. An optical network according to Claim 1 wherein the routing protocols for exchanging route information among the external IP networks are activated among the optical network control instances in the edge routers to which the external IP networks are connected.

20 3. An optical network according to Claim 1 or 2, wherein BGP's are used for protocols for exchanging the route information of the external IP networks.

4. An optical edge router, used for an optical network, for transmitting packets

25 between external IP networks and the optical edge router, comprising:

a section for transmitting the packets between neighboring routers in neighboring external IP networks;

a section for exchanging route information between the neighboring routers;

a section for producing a routing table and storing the produced routing table in

5 a storage section;

a section for collecting topology information existing in the optical network and storing the collected topology information in a storage section;

a section for signaling so as to establish/release optical paths;

a section for notifying route information to other optical edge routers which face
10 the optical edge router; and

a section for reading out the routing table and the topology information from the storage section and producing packet forwarding tables which set e.g., to where the packets are to be transmitted in the section for transmitting the packets.

15 5. A program, used for optical networks and optical edge routers having sections for predetermined calculations and sections for transmitting packets between the section for predetermined calculations and external IP networks, wherein the section for the predetermined calculations comprises functions of:

exchanging route information between neighboring routers in the external IP
20 networks;

producing a routing table and storing the produced routing table in a storage section;

collecting topology information inside the optical networks and storing the collected topology information in the storage section;

25 signaling so as to establish/release the optical paths;

notifying route information to other optical edge routers which face the optical edge router; and

reading out the routing tables and the topology information from the storage sections and producing a packet forwarding table which sets, e.g., where the packets are to be transmitted to by the section for transmitting the packets.

6. A cutting-through method for direct communication by a plurality of edge routers for connecting a core network and a plurality of external IP networks mutually at border points of the core network and the external IP networks, comprising:

maintaining lists, in which ingress-side IP address correspond to identifiers for showing outgoing interfaces of egress edge routers, in ingress edge routers;

adding the identifiers corresponding to the ingress-side IP address to the IP packets by the ingress edge routers when IP packets are transmitted;

transmitting the IP packets to the outgoing interfaces by referring to the identifiers added to the IP packets in the egress edge routers.

7. A cutting-through method according to Claim 6 wherein MPLS labels are used for the identifiers.

8. A cutting-through method according to Claim 6 wherein correspondence information with respect to the ingress-side IP address and its corresponding identifiers are exchanged among the edge routers by control signals.

9. An edge router comprising:

inputting sections for connecting a core network and a plurality of external IP

networks at border points mutually and handling incoming IP packets, inputted from the external IP networks, to the core network; and

outputting sections for handling outgoing IP packets outputted from the core network to the external IP networks, wherein

5 the inputting sections has:

a section for maintaining lists, in which ingress-side IP addresses correspond to identifiers for showing outgoing interfaces of other egress edge routers; and

a section for adding the identifiers corresponding to the ingress-side IP addresses of the IP packets to the IP packets, in accordance with the lists when the IP packets are
10 transmitted to other edge routers, and

the outputting section has a section for referring to the identifiers and transmitting the IP packets to the outgoing interfaces, indicated by the identifiers.

10. An edge router according to Claim 9 wherein MPLS labels are used for the
15 identifiers.

11. An edge router according to Claim 9, further comprising a section for exchanging information, in which the ingress-side IP addresses correspond to the identifiers, among other edge routers mutually by control signals, and wherein the section
20 for maintaining the lists has a section for generating or updating the lists in accordance with the information obtained by the exchanging section with respect to the correspondence information between the ingress-side IP addresses and the identifiers.

12. A program, installed to an information processing apparatus, for realizing
25 functions corresponding to edge routers, the functions being inputting functions, for

connecting a core network and a plurality of external IP networks at border points mutually and handling incoming IP packets inputted from the external IP networks to the core network; and outputting functions, for handling outgoing IP packets outputted from the core network to the external IP networks, wherein,

5 the inputting functions serve for:

 a function for maintaining lists in which ingress-side IP addresses correspond to identifiers for showing outgoing interfaces of other egress edge routers; and

 a function for adding the identifiers corresponding to the ingress-side IP addresses of the IP packets to the IP packets in accordance with the lists when the IP
10 packets are transmitted to other edge routers, and

 the outputting function serves for referring to the identifiers and transmitting the IP packets, indicated by the identifiers, to the outgoing interfaces.

13. A program according to Claim 12 wherein MPLS labels are used for the
15 identifiers.

14. A program according to Claim 12 further comprising a function for exchanging information, in which the ingress-side IP addresses correspond to the identifiers, among other edge routers mutually by control signals, and wherein the function for maintaining
20 the lists serves for generating or updating the lists in accordance with the information obtained by the exchanging section with respect to the correspondence information between the ingress-side IP addresses and the identifiers.

15. A recording medium, readable by the information processing apparatus, on
25 which the program according to Claim 12 is recorded.

16. An information transmission network system, having a plurality of line exchangers and a plurality of packet exchangers, for setting communication lines among the packet exchangers, the line exchangers and the packet exchangers being connected by communication lines, wherein,

the line exchangers have a line switch and a section for controlling line paths;

the line switch has a function for connecting the communication lines, connected to the line exchangers, arbitrarily;

each of the packet exchangers, connected to the line exchangers, has a packet switch, a section for controlling line paths, a section for controlling packet paths, and a cooperative control section;

the packet switch has functions for selecting communication lines for transmission and outputting in accordance with packet-ingress-side's information transmitted via the communication lines;

the sections for controlling line paths in the line exchangers are connected to the sections for controlling line paths in other line exchangers via lines among line exchangers;

the sections for controlling line paths in the packet exchangers are connected to at least the sections for controlling line paths in the line exchangers via lines among the packet exchangers and the line exchangers;

the sections for controlling line paths in the line exchangers and the sections for controlling line paths in the packet exchangers have a function for acknowledging line connection conditions in a communication network, by exchanging information of the communication conditions among the communication lines;

the section for controlling packet paths acknowledges

connection-related-information with respect to packet exchange among the packet exchangers connected via the communication lines, by exchanging the information for the packet paths via the communication lines, and determines the communication lines for output in accordance with the packet-ingress-side's information;

- 5 the cooperative control sections have functions for receiving instructions regarding new communication lines, referring to two pieces of information, i.e., connection information, with respect to line-exchanging-network, collected by the section for controlling line paths, and connection information with respect to packet-exchange collected by the section for controlling packet paths, selecting paths, 10 being used for the new communication lines, and instructing the section for controlling line paths to set paths being used for the new communication lines; and

- the section for controlling line paths has functions for transmitting messages to the line exchangers to set up lines in accordance with the instructed paths so that the line exchangers, receiving the messages for controlling and setting the connected lines, set up 15 the communication lines, and sending control messages to the line exchangers for setting the lines in accordance with the instructed paths.

17. An information transmission network system according to Claim 16, for setting the communication lines among the packet exchangers and packet/line exchangers, 20 having packet/line exchangers in which the packet exchangers and the line exchangers are integrated.

18. A packet exchanger in an information transmission network system, having a plurality of line exchangers and a plurality of packet exchangers, for setting 25 communication lines among the packet exchangers, comprising:

a packet switch having a function for selecting communication lines used for transmittance, in accordance with packet-ingress-side's information transmitted by the communication lines and outputting;

at least one section for controlling line paths in the line exchangers, connected to
 5 the communication lines among the packet exchangers/line exchangers, for exchanging connection information of the communication lines and acknowledging line connection condition in a communication network;

a section for controlling packet paths having functions for acknowledging connection-related-information with respect to packet exchange by exchanging
 10 information of the packet paths via the communication lines among the packet exchangers connected via the communication lines, and determining the communication lines for output; and

a cooperative control section having a function for receiving instructions by new communication lines, referring to two pieces of information, i.e., connection information,
 15 with respect to the packet exchange, collected by the section for controlling line paths, and connection information with respect to the packet exchange collected by the section for controlling packet paths, selecting paths used for the new communication lines, and instructing the section for controlling line paths to set paths used for the new communication lines; wherein

20 the section for controlling line paths have functions for transmitting messages to the line exchangers to set up lines in accordance with the instructed paths so that the line exchangers receive the messages for controlling and setting the connected lines, set up the communication lines, and send control messages to the line exchangers for setting the lines in accordance with the instructed paths.

19. A packet/line exchanger in an information transmission network system, having a plurality of line exchangers and a plurality of packet exchangers, for setting communication lines among the packet exchangers, comprising:

line switches, connected to the line exchangers, having a function for connecting
5 the communication lines arbitrarily;

a packet switch having function for selecting communication lines used for transmittance, in accordance with packet-ingress-side's information transmitted by the communication lines and outputting the same;

at least a section for controlling line paths in the line exchangers, connected to
10 the communication lines among the packet exchangers/line exchangers, for exchanging connection information of the communication lines and acknowledging line connection conditions in a communication network;

a section for controlling packet paths having functions for acknowledging connection-related-information with respect to packet exchange by exchanging
15 information of the packet paths via the communication lines among the packet exchangers connected via the communication lines, and determining a communication line for output; and

a cooperative control section having a function for receiving instructions by new communication lines, referring to two pieces of information, i.e., connection information,
20 with respect to the packet exchange, collected by the section for controlling line paths, and connection information with respect to the packet exchange collected by the section for controlling packet paths, selecting paths used for the new communication lines, and instructing the section for controlling line paths to set paths being used for the new communication lines; wherein

25 the section for controlling line paths has functions for transmitting messages to

the line exchangers to set up lines in accordance with the instructed path, instructed by the cooperative control section, so that the line exchangers, receive the messages for controlling and setting the connected lines, set up the communication lines, and send control messages to the line exchangers for setting the lines in accordance with the

5 instructed paths.